

Creation Date Oct-2013 Revision Date Oct-2018 Revision Number 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identification

Product Description: <u>Magnesium methoxide, 7-8% in methanol</u>

Product Grade: SQ Cat No. : Q2519C

Synonyms: Magnesium methylate

CAS-No: 109-88-6 Molecular Formula Mg(OCH3)2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Thermo Fisher Scientific India Pvt. Ltd

403-404, B-wing, Delphi, Hiranandani Business Park,

Powai, Mumbai 400076, INDIA.

E-mail address <u>laboratorysolutions@thermofisher.com</u>

1.4. Emergency telephone number

India Toll Free: 18 00 22 22 30 Chemtrec US: (800) 424-9300 Chemtrec EU: 001 (202) 483-7616

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 2 (H225) Self-heating substances/mixtures Category 1 (H251)

Health hazards

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Specific target organ toxicity - (single exposure)

Category 3 (H301)

Category 3 (H311)

Category 3 (H331)

Category 1 (H370)

Revision Date Oct-2018

Environmental hazards

Based on available data, the classification criteria are not met

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H251 - Self-heating: may catch fire

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H370 - Causes damage to organs

Precautionary Statements

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower

P235 + P410 - Keep cool. Protect from sunlight

P264 - Wash face, hands and any exposed skin thoroughly after handling

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician

P280 - Wear protective gloves/ protective clothing

P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing

P311 - Call a POISON CENTER or doctor/physician

P308 + P313 - IF exposed or concerned: Get medical advice/ attention

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS-No	EC-No.	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Methyl alcohol	67-56-1	200-659-6	92.50	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Methanol, magnesium salt	109-88-6	EEC No. 203-715-8	7.50	Flam. Sol. 2 (H228) Self-heat. 1 (H251) Acute Tox. 3 (H301)

Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)

Full text of Hazard Statements: see section 16

Magnesium methoxide, 7-8% in methanol

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Inhalation Move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Cool closed containers exposed to fire with water spray.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Revision Date Oct-2018

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

Carbon monoxide (CO), Carbon dioxide (CO2), Metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional ecological information. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe vapors or spray mist. Do not ingest. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): EU - Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. **UK** - EH40/2005 Containing the workplace exposure limits (WELs) for use with the Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended). Updated by September 2006 official press release and October 2007 Supplement. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m ³ TWA WEL -	TWA: 260 mg/m ³ 8 hr	TWA: 260 mg/m ³ 8 hr.
	STEL: 250 ppm STEL;	Skin	STEL: 600 ppm 15 min
	333 mg/m ³ STEL		STEL: 780 mg/m ³ 15 min
	_		Skin

Biological limit values

List source(s):

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) No information available

Route of exposure	Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Oral Dermal Inhalation				

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Safety glasses with side-shields (European standard - EN 166)

Hand Protection Protective gloves

Glove material		Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use In case of insufficient ventilation wear suitable respiratory equipment

Recommended Filter type: SCBA

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Colorless - Light yellow

Physical State Liquid

Odor Alcohol

Odor Threshold No data available

pH No information available

Melting Point/RangeNo data availableSoftening PointNo data availableBoiling Point/RangeNo information available

Flash Point 14 °C / 57.2 °F Method - No information available

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Liquid
Explosion Limits No data available

Vapor Pressure <=1100 hPa @ 50 °C

Vapor DensityNo data available(Air = 1.0)Specific Gravity / Density0.815 g/cm3@ 20 °CBulk DensityNot applicableLiquid

Water Solubility Immiscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
No data available
No data available

Explosive Properties No information available Vapors may form explosive mixtures with air

Oxidizing Properties No information available

9.2. Other information

Molecular FormulaMg(OCH3)2Molecular Weight86.38

SECTION 10: STABILITY AND REACTIVITY

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

10.1. Reactivity

Yes

10.2. Chemical stability

Moisture sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous Reactions 10.4. Conditions to avoid No information available. None under normal processing.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Acids. Oxidizing agents. Reducing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2). Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	Calc. ATE 60 mg/kg	Calc. ATE 60 mg/kg	Calc. ATE 0.6 mg/L (vapours)
	LD50 > 1187 – 2769 mg/kg (Rat	LD50 = 17100 mg/kg (Rabbit)	or 0.5 mg/L (mists)
)		LC50 = 128.2 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

(h) STOT-single exposure; Category 1

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; No data available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredness, nausea and vomiting

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to

contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl alcohol	Pimephales promelas:	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25
	LC50 > 10000 mg/L 96h			min
				EC50 = 40000 mg/L 15
				min
				EC50 = 43000 mg/L 5
				min

12.2. Persistence and degradability The product includes heavy metals. Prevent release into the environment. Special

pretreatment required

Persistence

Degradation in sewage

treatment plant

May persist, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10

12.4. Mobility in soil Spillage unlikely to penetrate soil The product is insoluble and floats on water Is not likely

mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Other adverse effects

Endocrine Disruptor Information Persistent Organic Pollutant

This product does not contain any known or suspected endocrine disruptors This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalogue, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not dispose of waste into sewer. Can be incinerated, when in compliance

with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1230
14.2. UN proper shipping name METHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

ADR

14.1. UN number UN1230
14.2. UN proper shipping name METHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

<u>IATA</u>

14.1. UN numberUN123014.2. UN proper shipping nameMETHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Transport in bulk according to Not applicable, packaged goods Annex II of MARPOL73/78 and the

Affilex II Of WARPOL/3

IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed.

Component	EINECS	ELINCS	NLP	TSCA	DSL	NDSL	PICCS	ENCS	IECSC	AICS	KECL
Methyl alcohol	200-659-6	-		Х	Х	-	Χ	Χ	Χ	Χ	Х
Methanol, magnesium salt	203-715-8	-		Х	-	Х	-	Χ	Χ	Χ	Х

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	
Methyl alcohol	500 tonne	5000 tonne	

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

National Regulations

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Methyl alcohol	WGK 1	

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment.

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H251 - Self-heating; may catch fire

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H370 - Causes damage to organs

H225 - Highly flammable liquid and vapor

H228 - Flammable solid

Legend

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

ENCS - Japanese Existing and New Chemical Substances

MARPOL - International Convention for the Prevention of Pollution from

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

PNEC - Predicted No Effect Concentration

EC50 - Effective Concentration 50% NOEC -

LD50 - Lethal Dose 50%

Transport Association

POW - Partition coefficient Octanol:Water PBT -

vPvB - very Persistent, very Bioaccumulative

VOC - Volatile Organic Compounds

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit TWA - Time Weighted Average IARC - International Agency for Research on Cancer

ACGIH - American Conference of Governmental Industrial Hygienists **DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

No Observed Effect Concentration

Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of ICAO/IATA - International Civil Aviation Organization/International Air

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Ships

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Magnesium methoxide, 7-8% in methanol

Revision Date Oct-2018

hygiene.

Creation Date Oct-2013 Next Revision Date Oct-2023

Revision Summary SDS section 1 updated and update of Format

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet